

## PRODUCT INFORMATION DISHCLOTHS (Nonwoven 73 gr)



The nonwoven 73 gr dishcloths are not fluffy (Air particule cleanliness Class 10000/ Clean Room ISO 7), soft and not abrasive, offer a high resistance in dry and wet conditions, remarkable capacity and speed of absorption (until 750% of its weight), an optimal water absorption, a high restitution capacity of solvents, thinners and cleaners, and thus an economical consumption. Certified food contact.

Biodegradable (more than 90% of cellulosic nature)

For hospitals and private hospitals, those dishcloths are printed with a colour code, allowing to distinguish them more easily, to avoid confusion, to reduce germs accumulation risk and to

avoid crossed contamination risks.

This product is printed only on one side.

| Description  | White      | Colour codes |           |           |           |
|--|------------|--------------|-----------|-----------|-----------|
|  |            | Yellow       | Pink      | Green     | Blue      |
| Format 300 x 300 mm – Fold in 4<br>Final format after folding 150 x 150 mm     | 0505/LV09  | 0525/LV10    | 0526/LV10 | 0527/LV10 | 0528/LV10 |
| Format 300 x 300 mm – Fold in 3 + 2<br>Final format after folding 100 x 150 mm | 0506/ LV11 | 0529/LV12    | 0530/LV12 | 0531/LV12 | 0532/LV12 |
| Format 300 x 400 mm – Fold in 4<br>Final format after folding 150 x 200 mm     | 0507/LV13  | 0533/LV14    | 0534/LV14 | 0535/LV14 | 0536/LV14 |
| Format 300 x 400 mm – Fold in 3 + 2<br>Final format after folding 100 x 200 mm | 0508/LV15  | 0537/LV16    | 0538/LV16 | 0539/LV16 | 0540/LV16 |



All our nonwoven quality have successfully passed the overall migration test into 3 liquids (distilled water, acetic acid, isooctane) in accordance with AFNOR Standard XP ENV 1186 - EEC Directives - 85/572 90/128 97/48 - Decree of 09/14/92. Our Non-woven can therefore perfectly be considered as adapted to food contact.



The trials carried out, according to the Drum Test Method (Helmke Drum) IES RP C 03/87T, indicate a release of 5485 particles for one moving sheet during one minute. In the testing conditions and according to the results, one sheet of our non-woven could be used in a room of mastered dust Class 10 000 (Federal Standard).

Do not hesitate to contact us for other formats.